





	COM		COM
1	COM	19	1A
2	.	20	1F
3	4E	21	1G
4	4D	22	2B
5	4C	23	2A
6	4DP	24	2F
7	3E	25	2G
8	3D	26	L
9	3C	27	3B
10	3DP	28	3A
11	2E	29	3F
12	2D	30	3G
13	2C	31	4B
14	2DP	32	4A
15	1E	33	4F
16	1D	34	4G
17	1C	35	.
18	1B	36	COM

- NOTE: 1. TN TYPE  
 2. DRIVING METHOD: STATIC  
 3. OPERATING VOLTAGE: 3.0 V  
 4. OPERATING TEMP:  $-0 \sim 50^{\circ}\text{C}$   
 5. STORAGE TEMP:  $-5 \sim 60^{\circ}\text{C}$   
 6. VIEWING DIRECTION: 6:00  
 7. POLARIZER MODE: REFLECTIVE POSITIVE  
 8. CONNECTION: ZEBRA TYPE  
 9. DIMENSIONS ARE IN MILLIMETERS AND UNLESS OTHERWISE NOTED ARE  $\pm 0.20\text{MM}$

1				
REV.	MODIFY CONTENT			DATE
DWN	Bauing	UNIT	mm	CUST. MODEL
CKD		SCALE		MODEL MCD-729/Z8R1G
APPD		$\phi$	DATE	FEB-02-05
<b>ALL SHORE INDUSTRIES, INC</b>				NAME MCD-729
				PAGE 2/2